

IBC BERM



*L-bracket stays can be positioned inwards or outwards. The above image displays both positions for reference only.

48-452-YE-SS

Dimensions	4 ft. x 5 ft. x 2 ft. (1.2 m. x 1.5 m. x 0.6 m.)
Weight	84 lbs. (38.1 kg.)
Spill Capacity	229 gal. (1,131.8 L)

48-552-YE-SS

Dimensions	5 ft. x 5 ft. x 2 ft. (1.5 m. x 1.5 m. x 0.6 m.)
Weight	102 lbs. (46.3 kg.)
Spill Capacity	374 gal. (1,415.7 L)

48-462-YE-SS

Dimensions	4 ft. x 6 ft. x 2 ft. (1.2 m. x 1.8 m. x 0.6 m.)
Weight	89 lbs. (49.4 kg.)
Spill Capacity	359 gal. (1,359 L.)

Regulations: EPA 40 CFR 264.175, SPCC, NPDES

STEEL IBC TOTE SPILL PALLET

9469-BD

Dimensions	72 in. x 53 in. x 28 in. (182.9 cm. x 134.6 cm. x 71.1 cm.)
Weight	620 lbs. (281.3 kg.)
Spill Capacity	385 gal. (1,457.4 L.)
Load Capacity	5,000 lbs. (2,268 kg.)

Regulations: EPA 40 CFR 264.175, SPCC, NPDES



STEEL DOUBLE IBC TOTE SPILL PALLET

9480-BD

Dimensions	120 in. x 53 in. x 26 in. (304.8 cm. x 134.6 cm x 66 cm.)
Weight	1,020 lbs. (462.7 kg.)
Spill Capacity	385 gal. (1,457.4 L.)
Load Capacity	10,000 lbs. (4,535.9 kg.)

Regulations: EPA 40 CFR 264.175, SPCC, NPDES



 = Black Diamond

Disclaimer: The load capacity is based on a Uniformly Distributed Load (UDL).