

ADJUSTABLE FRAME ROUND, CONE STYLE



ROUND, CONE STYLE

Cone Depth	18 in. (45 cm.)
Weight	2 lbs. (0.9 kg.)
Flow Rate	90 gal. (340.69 L.) per min. per sqft.
Load Capacity	40 lbs (18.1 kg.)
Patent	US Patent No. 10,384,155

PART NUMBER	DESCRIPTION	DIAMETER IN. (CM.)		ABSORB CAPACITY GAL. (L.)
		MIN.	MAX.	
4340-CONE	Standard	25 (63.5)	28 (71)	N/A
4340-CONE-NO	No Overflow	25 (63.5)	28 (71)	N/A
4340-CONE-IB	With Oil-Absorbing Packets	25 (63.5)	28 (71)	0.23 (0.87)
4340-22-CONE	Standard	22 (56)	24 (61)	N/A
4340-22-CONE-NO	No Overflow	22 (56)	24 (61)	N/A
4340-22-CONE-IB	With Oil-Absorbing Packets	22 (56)	24 (61)	0.23 (0.87)

Regulations: 40 CFR 122.26, EPA, SPCC, NPDES

ADJUSTABLE FRAME ROUND, BAG STYLE



ROUND, BAG STYLE

Bag Depth	14 in. (35.6 cm.)
Weight	2 lbs. (0.9 kg.)
Flow Rate	90 gal. (340.69 L.) per min. per sqft.
Load Capacity	40 lbs. (18.1 kg.)
Patent	US Patent No. 10,384,155

PART NUMBER	DESCRIPTION	DIAMETER IN. (CM.)		ABSORB CAPACITY GAL. (L.)
		MIN.	MAX.	
4340	Standard	25 (63.5)	28 (71)	N/A
4340-NO	No Overflow	25 (63.5)	28 (71)	N/A
4340-IB	With Oil-Absorbing Packets	25 (63.5)	28 (71)	0.23 (0.87)
4340-22	Standard	22 (56)	24 (61)	N/A
4343-22-NO	No Overflow	22 (56)	24 (61)	N/A
4343-22-IB	With Oil-Absorbing Packets	22 (56)	24 (61)	0.23 (0.87)

Regulations: 40 CFR 122.26, EPA, SPCC, NPDES