MODULAR DIVERTER BERM

Divert spilled liquids away from walkways and drains or capture them in a designated area. These diverter berms can connect together to build a berm barrier on site with ease.



15'L STRAIGHT SECTION

	48-215-DB	
Dimensions	15 ft. x 2 in. (4.6 m. x 5.1 cm.)	
Weight	3 lbs. (1.4 kg.)	

Regulations: EPA, SPCC and NPDES

25'L STRAIGHT SECTION

	48-225-DB	
Dimensions	25 ft. x 2 in. (7.6 m. x 5.1 cm.)	
Weight	8 lbs. (3.6 kg.)	

Regulations: EPA, SPCC and NPDES

50'L BERM KIT

48-250-DBKIT		
Dimensions	50 ft. x 2 in. (15.2 m. x 5 cm.)	
Weight	26 lbs. (11.7 kg.)	
Kit Includes	(2) 25' Straight Sections, (4) 12" Corner Sections, (6) Sili-Thane Sealant Cartridges, (1) 8 oz. Vinyl Cement, (1) Berm Repair Material Roll	

Regulations: EPA 40 CFR 112.7, 40 CFR 122.26, 40 CFR 264.175, SPCC and NPDES $\,$











12" CORNER SECTION

	48-2CORNER-DB
Dimensions	4.5 in. x 2 in. [11.4 cm. x 5.1 cm.]
Length	12 in. (30.5 cm.) (From Corner to End, Long side)
Weight	1 lb. (0.4 kg.)

Regulations: EPA, SPCC and NPDES



10" WALL SECTION

40 OWALL DR			
	48-2WALL-DB		
Dimensions	4.8 in. x 2 in. (12.1 cm. x 5.1 cm.)		
Length	7 in. (17.7 cm.) (From Corner to End) 3 in. (7.6 cm.) From Corner up the Wall)		
Weight	1 lb. (0.4 kg.)		
egulations: EPA,	SPCC and NPDES		

12'L DRIVE-OVER KIT

48-212-BK-DBKIT		
Dimensions	12 ft. x 2 in. (3.7 m. x 5.1 cm.)	
Weight	12 lbs. (5.4 kg.)	

Regulations: EPA, SPCC and NPDES

