

FRAMELESS CATCH BASIN INSERTS

NON-WOVEN, CONE STYLE



NON-WOVEN, CONE STYLE	
Cone Depth	18 in. (45 cm.)
Weight	2 lbs. (0.9 kg.)
Flow Rate	90 gal. (340.69 L.) per min. per sqft.
Load Capacity	40 lbs. (18.1 kg.)

PART NUMBER	DESCRIPTION	DIMENSIONS [LxW] IN. [CM.]	ABSORB CAPACITY GAL. [L.]
4320	Standard	36 x 48 (91 x 122)	N/A
4320-NO	No Overflow	36 x 48 (91 x 122)	N/A
4320-IB	With Oil-Absorbing Packets	36 x 48 (91 x 122)	0.23 (0.87)
4326	Standard	60 x 60 (152 x 152)	N/A
4326-NO	No Overflow	60 x 60 (152 x 152)	N/A
4326-IB	With Oil-Absorbing Packets	60 x 60 (152 x 152)	0.23 (0.87)

Regulations: 40 CFR 122.26, EPA, SPCC, NPDES

STORM SENTINEL® FRAMELESS INSTALL




1. Safely remove the grate.



2. Insert the Storm Sentinel® into the recess.



3. Hold the fabric in place until the grate is returned.



4. Trim the excess fabric with a knife or scissors if desired.