

20-GALLON SALVAGE DRUM



1220-YE

Top Diameter	22.25 in. (56.5 cm.)
Bottom Diameter	18 in. (45.7 cm.)
Height	19 in. (22.9 cm.)
Weight	10.5 lbs. (47.8 kg.)
Spill Capacity	20 gal. (75.7 L.)
Load Capacity	166 lbs. (75.3 L.)

Regulations: UN 1H2/X295/S, DOT 49 CFR 173.3(c), EPA, SPCC and NPDES



30-GALLON SALVAGE DRUM



1230-YE

Top Diameter	22.25 in. (56.5 cm.)
Bottom Diameter	18 in. (45.7 cm.)
Height	30 in. (76.2 cm.)
Weight	13.5 lbs. (6.1 kg.)
Spill Capacity	30 gal. (113.6 L.)
Load Capacity	220 lbs. (99.8 kg.)

Regulations: UN 1H2/X295/S, DOT 49 CFR 173.3(c), EPA, SPCC and NPDES



65-GALLON SALVAGE DRUM



1065-YE

Top Diameter	27.75 in. (70.5 cm.)
Bottom Diameter	23 in. (58.4 cm.)
Height	37.5 in. (95.3 cm.)
Weight	43 lbs. (19.6 kg.)
Spill Capacity	65 gal. (246.1 L.)
Load Capacity	440 lbs. (199.6 kg.)

Regulations: UN 1H2/X295/S, DOT 49 CFR 173.3(c), EPA, SPCC and NPDES



95-GALLON SALVAGE DRUM



1095-YE

Top Diameter	31.5 in. (80 cm.)
Bottom Diameter	25.88 in. (65.8 cm.)
Height	40 in. (102.2 cm.)
Weight	47 lbs. (21.3 kg.)
Spill Capacity	95 gal. (359.6 L.)
Load Capacity	650 lbs. (295 kg.)

Patents US Patent No. 9,592,927
CA Patent No. 2,699,046

Regulations: UN 1H2/X295/S, DOT 49 CFR 173.3(c), EPA, SPCC and NPDES



95-GALLON ENVIROSALV SALVAGE DRUM



1295-YE

Top Diameter	32 in. (81.3 cm.)
Bottom Diameter	26 in. (66 cm.)
Height	44 in. (111.8 cm.)
Weight	56 lbs. (25.4 kg.)
Spill Capacity	95 gal. (359.6 L.)
Load Capacity	650 lbs. (295.8 kg.)

Regulations: UN 1H2/X295/S, DOT 49 CFR 173.3(c), EPA, SPCC and NPDES



103-GALLON SALVAGE DRUM



1040-YE

Top Diameter	31.5 in. (80 cm.)
Bottom Diameter	25.75 in. (65.5 cm.)
Height	45 in. (114.3 cm.)
Weight	49 lbs. (22.3 kg.)
Spill Capacity	103 gal. (389.9 L.)
Load Capacity	650 lbs. (295.8 kg.)

Patents US Patent No. 9,592,927
CA Patent No. 2,699,046

Regulations: UN 1H2/X295/S, DOT 49 CFR 173.3(c), EPA, SPCC and NPDES

