ENPAC

SIMPLE. RUGGED. **AFFORDABLE.**

ALUMINUM L-BRACKET BERM



Featuring highly chemical-resistant fabric and removable aluminum stays, the Aluminum L-Bracket Berm offers a cost-effective alternative to comparable spill containment berms.

19 Standard Sizes and Custom Options (see p.2)



QUICK ASSEMBLY



EASY ENTRY & EXIT



FULLY CONTAIN EQUIPMENT & TRUCKS


KEY FEATURES

- First-class chemical, rip, tear, and puncture resistance
- Easy, fast setup with economical price
- Compact storage and transport
- Drive-over sidewalls with bracket removal

- Aluminum L-Bracket Spill Containment Berm
- 48-GP: Ground Pad for Spill Containment Berms
- 48-TM: TracMat for Spill Containment Berms

ACCESSORIES

TracMat (1) and Ground Pad (2) are available to protect and prolong the life of the spill berm.



PROTECTING PEOPLE, PROPERTY, AND OUR PLANET.

GLOBAL LEADER in spill containment solutions

TRUSTED QUALITY Engineered for safety and performance

FAST & RELIABLE Shipping solutions to meet your needs

EXPERT SUPPORT Dedicated team ready to help

1-800-9ENPAC9 | info@ENPAC.com | www.ENPAC.com

SIZES AND USES (custom available)

Small sizes commonly contain light plants, generators, light equipment, 55-gallon drums, and IBCs.

Medium sizes include containment for medium-size equipment, small vehicles, IBCs, and machinery.

Large sizes commonly contain large tankers, military vehicles, large equipment, and bulk storage of drums/IBCs.



CUSTOM SIZES AVAILABLE

Part Number	Containment Dimensions L x W x H	Spill Capacity
BD-44-AL-L	4 x 4 x 1 ft (1.2 x 1.2 x 0.3 m)	119 gal (450 L)
BD-46-AL-L	4 x 6 x 1 ft (1.2 x 1.8 x 0.3 m)	179 gal (677 L)
BD-55-AL-L	5 x 5 x 1 ft (1.5 x 1.5 x 0.3 m)	187 gal (707 L)
BD-68-AL-L	6 x 8 x 1 ft (1.8 x 2.4 x 0.3 m)	359 gal (1,358 L)
BD-810-AL-L	8 x 10 x 1 ft (2.4 x 3 x 0.3 m)	598 gal (2,263 L)
BD-1010-AL-L	10 x 10 x 1 ft (3 x 3 x 0.3 m)	748 gal (2,831 L)
BD-1020-AL-L	10 x 20 x 1 ft (3 x 6.1 x 0.3 m)	1,496 gal (5,662 L)
BD-1030-AL-L	10 x 30 x 1 ft (3 x 9.1 x 0.3 m)	2,244 gal (8,494 L)
BD-1040-AL-L	10 x 40 x 1 ft (3 x 12.2 x 0.3 m)	2,992 gal (11,325 L)
BD-1050-AL-L	10 x 50 x 1 ft (3 x 15.2 x 0.3 m)	3,740 gal (14,157 L)
BD-1060-AL-L	10 x 60 x 1 ft (3 x 18.3 x 0.3 m)	4,488 gal (16, 988 L)
BD-1212-AL-L	12 x 12 x 1 ft (3.6 x 3.6 x 0.3 m)	1,077 gal (4,077 L)
BD-1220-AL-L	12 x 20 x 1 ft (3.6 x 6.1 x 0.3 m)	1,795 gal (6,795 L)
BD-1226-AL-L	12 x 26 x 1 ft (3.6 x 7.9 x 0.3 m)	2,334 gal (8,835 L)
BD-1230-AL-L	12 x 30 x 1 ft (3.6 x 9.1 x 0.3 m)	2,692 gal (10,190 L)
BD-1236-AL-L	12 x 36 x 1 ft (3.6 x 11 x 0.3 m)	3,231 gal (12,230 L)
BD-1250-AL-L	12 x 50 x 1 ft (3.6 x 15.2 x 0.3 m)	4,488 gal (16,989 L)
BD-1440-AL-L	14 x 40 x 1 ft (4.2 x 12.2 x 0.3 m)	4,189 gal (15,857 L)
BD-1550-AL-L	15 x 50 x 1 ft (4.5 x 15.2 x 0.3 m)	5,654 gal (21,402 L)

*The berm capacity is based on dimensions, low flow rate, a level surface, and no displaced volume.
Regulations: EPA 40 CFR 264.175, SPCC, NPDES

ENPAC

www.ENPAC.com