

20-Gallon Water Scrubber

Oil-Water Separators allow water to flow through, while separating out oils from industrial wastewater, process water, or stormwater.

Connect a hose to the top of the lid and open the bottom drain to allow oil-free water to pass through.

Oil-Absorbing Spilltration® technology is specifically designed to remove oily sheen from stormwater, while also preventing sediment and debris.



KEY FEATURES

- ✓ Filter sediment, debris, and oils to allow clean water to flow
- ✓ UV resistant
- ✓ Standard 1" NPT lid bulkhead fitting for hoses or piping
- ✓ Lid can be used as a funnel with bulkhead removed
- ✓ Zero-release version available with oil-absorbing packets or Bazooka
- ✓ Refill kit available
- ✓ Bulkhead fittings and additional oil-absorbing accessories are customizable to your application



★ KIT INCLUDES

- ★ (1) 20-Gallon Salvage Drum*
- ★ (1) 3/4" NPT Drain
- ★ (1) 1" NPT Lid Bulkhead
- ★ (15) Oil-Absorbing Spilltration® Pads
- ★ (2) Disposal Bags and Ties

**Cannot be used for transportation or waste receptacle of hazardous materials.*



★ SPECIFICATIONS

- ★ **Dimensions (LxWxH):** 22.25"x22.25"x19"
- ★ **Weight:** 15 lbs.
- ★ **Spill Capacity:** 20 gal.
- ★ **Load Capacity:** 166 lbs.
- ★ **Absorb. Capacity (per piece):** 68.9 fl. oz.
- ★ **Absorb. Capacity:** 8.1 gal.
- ★ **Flow Rate:** 10 gal./min.
- ★ **Volume Capacity (Lid Used as Funnel):** 4.5 gal.
- ★ **Regulations:** EPA 40 CFR 112.7, EPA 40 CFR 122.26, SPCC, NPDES



SKU: 43-20-WS

Refill Kit SKU: 43-20-WS-RF