

Frameless Storm Sentinel® Catch Basin Insert - Cone Style



Part Number	Description	Dimensions in. (cm.)	Absorption Capacity gal. (L.)
4320	Sediment, Trash, & Debris	36x48 (91x122)	N/A
4326	Sediment, Trash, & Debris	60x60 (152x152)	N/A
4320-NO	Sediment, Trash, & Debris, No Overflow	36x48 (91x122)	N/A
4326-NO	Sediment, Trash, & Debris, No Overflow	60x60 (152x152)	N/A
4320-IB	Sediment, Trash, Debris, & Oils	36x48 (91x122)	0.23 (0.87)
4326-IB	Sediment, Trash, Debris, & Oils	60x60 (152x152)	0.23 (0.87)

Installation (requires two people):

1. Remove catch basin grate.
2. Remove dirt and debris from grate and basin edges.
3. Insert filter and place grate on top of one end to hold it in place.
4. Reinstall grate. To ensure maximum effectiveness, fabric of filter should be fully captured between grate and edge of basin.
5. If desired, use a utility knife to cut excess fabric around the grate.

*If oil version was purchased, oil absorbing packet is replaceable.

Removal:

1. Lift one end of catch basin grate while keeping the other side on ground. This keeps the storm drain filter from falling into hole.
2. Secure the storm drain filter by holding yellow straps. The catch basin grate can now be fully removed from the storm drain filter.
3. Lift and remove storm drain filter using straps.
4. Dispose of contaminated Storm Sentinels® according to all local, state and federal regulations. Contact your local disposal authority for more information.
5. Replace and install new filter.

