

Adjustable Frame Storm Sentinel® Catch Basin Insert - Round, Bag Style



| Part Number | Description | Diameter in. (cm.) | Absorption Capacity gal. (L.) |
|----------------|--|-------------------------|----------------------------------|
| 4340 | Sediment, Trash, & Debris | 25 (63.5) up to 28 (71) | N/A |
| 4340-22 | Sediment, Trash, & Debris | 22 (56) up to 24 (61) | N/A |
| 4340-NO | Sediment, Trash, & Debris, No Overflow | 25 (63.5) up to 28 (71) | N/A |
| 4340-22-NO | Sediment, Trash, & Debris, No Overflow | 22 (56) up to 24 (61) | N/A |
| 4340-IB | Sediment, Trash, Debris, & Oils | 25 (63.5) up to 28 (71) | 0.23 (0.87) |
| 4340-22-IB | Sediment, Trash, Debris, & Oils | 22 (56) up to 24 (61) | 0.23 (0.87) |

| Installation: | Removal: | |
|--|--|--|
| 1. Remove catch basin grate. | 1. Remove catch basin grate. | |
| 2. Remove dirt and debris from grate and basin | 2. Lift and remove storm drain filter using yellow straps. | |
| edges. | 3. Dispose of contaminated Storm Sentinels® according | |
| 3. Place the filter over the grate and adjust the wire | to all local, state and federal regulations. Contact your | |
| frame to fit the outside edges. | local disposal authority for more information. | |
| 4. Place the wire frame inside the edge and hang | 4. Replace and install new filter. | |
| fabric inside basin. | | |
| 5. Adjust the frame as necessary to fit into the corners | | |
| of the basin lip. | | |
| 6. Reinstall grate. | | |
| | | |
| *If oil version was purchased, oil absorbing | | |
| packet is replaceable. | | |



By: R.R.