

## Adjustable Frame Storm Sentinel® Catch Basin Insert - Round, Cone Style



Part Number	Description	Diameter in. (cm.)	Absorption Capacity gal. (L.)
4340-CONE	Sediment, Trash, & Debris	25 (63.5) up to 28 (71)	N/A
4340-22-CONE	Sediment, Trash, & Debris	22 (56) up to 24 (61)	N/A
4340-NO-CONE	Sediment, Trash, & Debris, No Overflow	25 (63.5) up to 28 (71)	N/A
4340-22-NO-CONE	Sediment, Trash, & Debris, No Overflow	22 (56) up to 24 (61)	N/A
4340-CONE-IB	Sediment, Trash, Debris, & Oils	25 (63.5) up to 28 (71)	0.23 (0.87)
4340-22-IB-CONE	Sediment, Trash, Debris, & Oils	22 (56) up to 24 (61)	0.23 (0.87)

## Installation:

- 1. Remove catch basin grate.
- 2. Remove dirt and debris from grate and basin edges.
- 3. Place the filter over the grate and adjust the wire frame to fit the outside edges.
- 4. Place the wire frame inside the edge and hang fabric inside basin.
- 5. Adjust the frame as necessary to fit into the corners of the basin lip.
- 6. Reinstall grate.

\*If oil version was purchased, oil absorbing packet is replaceable.

## Removal:

- 1. Remove catch basin grate.
- 2. Lift and remove storm drain filter using yellow straps.
- 3. Dispose of contaminated Storm Sentinels® according to all local, state and federal regulations. Contact your local disposal authority for more information.
- 4. Replace and install new filter.



Rev. 03 By: R.R. Date: 12/16/2024