

## Storm Sentinel® Curb Inlet Filter



Part Number	Description	Dimensions in. (cm.)
4346	Sediment, Trash, & Debris	5 Dia. x 48 L. (12 x 122)
4346-IB	Sediment, Trash, Debris, & Oils	5 Dia. x 48 L. (12 x 122)
4345-BX2	Weighted Filter Bags, Box of 2	4 x 15 x 4 (10 x 38 x 10)

### Curb Inlet Only with Weighted Bags



### Curb & Drop Inlet



#### Installation (weighted bags are required):

1. Position the filter coil (4346) against the curb inlet. The edges of the coil should extend beyond the opening on both sides.
2. The skirt is not required and can be removed or wrapped around the filter coil.
3. Position weighted filter bags (4345-BX2, sold separately), or other weights (such as sandbags), on each end of the coil. ENPAC weighted bags are secured with hook and loop strips.
4. Check that there are no gaps between the coil and the ground. Add more weight if necessary to ensure effective filtration.

#### Removal:

1. Lift and remove the coil and weighted bags.
2. Dispose of contaminated Storm Sentinels® according to all local, state and federal regulations. Contact your local disposal authority for more information.
3. Replace and install new filter.

#### Installation (weighted bags are not required):

1. Remove catch basin grate.
2. Remove dirt and debris from grate and basin edges.
3. Position the filter coil (4346) against the curb inlet. The edges of the coil should extend beyond the opening on both sides.
4. Position the skirt to the end of the catch basin.
5. Reinstall grate. To ensure maximum effectiveness, fabric of filter should be fully captured between grate and edge of basin.
6. If desired, use a utility knife to cut excess fabric around the grate.
7. For full filtration of the combination drain (curb and drop inlet), pair the Curb Inlet Filter (4346) with a Catch Basin Insert (4320), or purchase a one-piece combo version, the Curb Basin Insert (4320-CURB).

#### Removal:

1. Remove catch basin grate.
2. Lift and remove the filter.
3. Dispose of contaminated Storm Sentinels® according to all local, state and federal regulations. Contact your local disposal authority for more information.
4. Replace and install new filter.