

Salvage Drum Dolly Product Instructions SKU: 8050

ATTENTION: TO ENSURE SAFE AND EASY USE OF YOUR ENPAC DRUM DOLLY, READ THESE INSTRUCTIONS BEFORE USING.

General Safety Information

This drum dolly is intended for the transport of ENPAC® Salvage Drums: 1230-YE, 1065-YE, 1295-YE, 1095-YE, and 1040-YE.

This drum dolly can also be used with industry standard 30, 55, and 85-gallon steel or poly drums.

Adhere to the following instructions to ensure safe and proper use.

1. Maximum load capacity - 900 lbs. (408.2 kg.)
2. Do NOT exceed rated capacity. Injury to persons or property may result from overloading and misuse.
3. Do NOT use on inclines.
4. Ensure all bolts are completely tightened before use.
5. Periodically check for loose or worn hardware, replace any at once.
6. Do NOT operate a damaged unit until it is completely repaired.
7. Warranty is voided if custom alterations to the drum dolly are not made at the factory.

Check all contents before installation. Contents:

- (1) Drum Dolly
- (4) Caster Wheels
- (16) Carriage Bolts (1/4"-20 x 3/4")
- (16) Washers (1/4" SAE)
- (16) Nuts (1/4"-20)

Wheel Assembly Instructions

1. Place the dolly carefully on a level surface with the rim side down.
2. Place the Caster on top of the Cross Brace (4) hole pattern.
3. Insert one Carriage Bolt through the far side and attach the Washer and Nut (as shown below).
4. Repeat step 3 until all Casters are secured to the dolly.
5. Ensure all bolts are tightened before use.

