

## Drain Cover Instructions



### Installation:

1. Make sure the drain cover is the correct size. For best results, the drain cover should be 6" larger than the outside of the drain.
2. Remove dirt and debris from the drain.
3. The plastic film should be saved for reuse. Remove the plastic film and store it for later.
4. Center the drain cover over the drain, grate, or manhole.
5. For a faster seal, you may step on the drain cover. Do **NOT** attempt this if the spill has already reached the drain.

### After-Care Instructions:

1. Always wash the drain cover for reuse or storage. The drain cover can be washed in warm water with a non-abrasive detergent or petroleum solvent cleaner. **NOTE:** Always follow your state and local regulations regarding proper decontamination and waste handling procedures if the drain seal comes into contact with hazardous chemicals. Thoroughly dry with a cloth and re-apply plastic film.
2. The drain cover, with plastic film, can be rolled and stored back into the box. Do **NOT** store without plastic film.
3. Do **NOT** store the drain cover in direct sunlight.
4. Do **NOT** store in high humidity or where temperatures exceed 120° F (48.8° C).
5. Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions such as temperature, humidity, and UV radiation. Typical product life expectancy is 5 years. Inspect the stored product regularly to ensure it is in a usable state.
6. Some chemicals will degrade this product.
7. Dispose of unusable or contaminated drain covers according to all local, state and federal regulations. Contact your local disposal authority for more information.

### Chemical Compatibility:

Acetone	Good	Ethanol (95%)	Good	Isopropyl Alcohol	Good
Antifreeze	Good	Gasoline	Good	Mineral Oil	Good
Chlorine Bleach (5% Sodium Hypochlorite)	Good	Hydraulic Fluid	Good	Sodium Hydroxide (40%)	Good
Chlorine Standard Solution (1000ppm)	Good	Hydrochloric Acid (18.5%)	Fair	Sulfuric Acid (50%)	Fair
Diesel Fuel	Good	Hydrogen Peroxide (30%)	Fair	Xylene	Fair