

Envirosalv Lockable 95-Gallon Poly-Overpack® Salvage Drum

Security Clip Installation Instructions

The following instructions are being provided if the Lock Down Kit is being utilized with the Envirosalv Lockable 95-Gallon Poly-Overpack® Salvage Drum, SKU 1295-YE.

The Lock Kit consists of a Locking Clip, Security Screw, Security Screw Wrench, and a Data tag (Fig. 4.)

Fig. 1



Fig. 2



Fig. 3



Fig. 4



- 1) Remove contents from the sealed bag and verify that the required components are included, see Fig. 4.
- 2) Fill out the included Security and Tracking tag that is included. Use a permanent marker or other writing utensil to help prevent erasure or removal of information.
- 3) First, attach the Locking Clip as shown in Fig. 1 and 2. Clip the lower portion to the bottom of the lid where shown, and then push the upper portion of the clip forward until it “snaps” into the recess on the top of the lid.
- 4) Then, tighten the lid as instructed on the POLY-OVERPACK® AND WHEELED POLY-OVERPACK® SALVAGE DRUM PACKAGING LIMITATIONS AND CLOSURE INSTRUCTIONS supplied with the Envirosalv drum, 1295-YE.
- 5) Once the lid is tightened to the correct location, install the security screw through the Data tag, and then through the clip hole, making sure that the screw secures both items before being threaded into the insert.
- 6) Lastly, tighten using the included wrench as shown in Fig. 3.
- 7) The unit is now complete and ready for disposal, shipping, storage, etc.

NOTE: the Locking Clip is **NOT** to be used as a handle.

NOTE: As a precaution, **DO NOT** leave the Security Wrench near the drum. This will help to prevent unauthorized access to the sealed unit.

If there are any questions regarding proper installation or use, please contact ENPAC LLC Customer Service at 1-800-936-7229