



SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: POLYPROPYLENE ABSORBENTS

PRODUCT USE: SORBENT MEDIA USED TO ABSORB LEAKS AND SPILLS WHICH INCLUDE BUT NOT LIMITED TO OIL, WATER, COOLANTS AND SOLVENTS

SPECIFIC PRODUCT TYPE: ABSORBENT PADS

COMPANY INFORMATION: ENPAC, LLC
34355 MELINZ DRIVE
EASTLAKE, OH 44095

PHONE: 440-975-0070
FAX: 440-975-0047
EMER: 440-975-0070

SECTION 2: HAZARDS IDENTIFICATION

THIS PRODUCT IS NOT DANGEROUS IN ITS UNUSED FORM AND CONTAINS NO HAZARDOUS INGREDIENTS. NOT WHMIS REGULATED.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

MATERIALS	PERCENT	CAS #
POLYPROPYLENE:	>97%	9003-07-0
SURFACTANT:	< 1%	9004-34-6
GRAY PIGMENT	< 1%	NONE
YELLOW PIGMENT	< 1%	NONE
GREEN PIGMENT	< 1%	NONE
ORANGE PIGMENT	< 1%	NONE

SECTION 4: FIRST AID MEASURES

NO SPECIAL PROCEDURES REQUIRED

SECTION 5: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >315 DEGREES CELCIUS (ASTM D93)

FLAMMABLE LIMITS: NOT YET DETERMINED

EXTINGUISHING MEDIA: WATER, FOAM, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: STANDARD PROCEDURE FOR CLASS A FIRES

UNUSUAL FIRE AND EXPLOSION HAZARD: SOME CARBON MONOXIDE UNDER LEAN OXYGEN CONDITIONS

SECTION 6: ACCIDENTAL RELEASE MEASURES

NO SPECIAL STEPS ARE TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

SECTION 7: HANDLING AND STORAGE

STORE IN DRY AREA. DO NOT STORE NEAR OPEN FLAME, HIGH HEAT OR STRONG OXIDANTS. POLYPROPYLENE, WHEN HEATED, BECOMES VERY STICKY AND WILL BURN. USE SELF-CONTAINED AIR MASK TO ENTER SMOKY AREA IN THE EVENT OF FIRE.

SECTION 8: EXPOSUR CONTROLS/PERSONAL PROTECTIVE EQUIPMENT

EXPOSURE LIMITS: OSHA PEL: N/A

ACGIH TLV: N/A

RESPIRATORY PROTECTION: NONE REQUIRED

VENTILATION: NONE REQUIRED

PROTECTIVE GLOVES: NONE REQUIRED ONLY IF MOLTAN

EYE PROTECTION: NONE REQUIRED

OTHER PROTECTIVE EQUIPMENT (SPECIFY): NONE REQUIRED

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

COLOR: GRAY, YELLOW, GREEN, ORANGE

DENSITY: 0.04 - 0.06 gram/cc

ODOR: CITRUS (IN ORANGE ABSORBENT)

SPECIFIC GRAVITY: 0.88 - 0.92

FLASH POINT: NOT APPLICABLE

BOILING POINT: NOT APPLICABLE

MELTING POINT: > 160 DEGREES CELSIUS

SOLUBILITY IN WATER:	INSOLUABLE
PERCENT VOLATILE:	NOT APPLICABLE
EVAPORATION RATE:	NOT APPLICABLE
VAPOR PRESSURE (mm Hg):	NOT APPLICABLE
VAPOR DENSITY (Air = 1):	NOT APPLICABLE
AUTO IGNITION TEMPERATURE	>675 DEGREES FAHRENHEIT

SECTION 10: STABILITY AND REACTIVITY DATA

STABILITY:	STABLE
INCOMPATIBILITY (conditions to avoid):	NONE
INCOMPATIBILITY (materials to avoid):	NITRIC ACID, PERCHLORIC ACID, SULFURIC ACID OR 98% SULFURIC ACID
HAZARDOUS DECOMPOSITON:	WHEN HEATED, IT MAY EMIT TOXIC
HAZARDOUS POLYMERAZATION:	WILL NOT OCCUR

SECTION 11: TOXOCOLOGICAL INFORMATION

HEALTH HAZARDS (acute or cronic):	NONE
SIGNS OR SYSMTOMS OF EXPOSURE:	NONE
MEDICAL CONDITIONS GENERRALLY AGGRAVATED BY EXPOSURE:	NONE
DATE ISSUED:	January 1, 2018
PREPARED BY:	ENPAC, LLC

SECTION 12 TO SECTION 15 NOT APPLICABLE

SECTION 16: OTHER INFORMATION

SDS PREPARATION DATE: January 1, 2018

THE INFORMATION CONTAINED HEREIN IS ACCCURATE TO THE BEST OF MY KNOWLEDGE. MY COMPANY MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE SAFE USE OF THIS MATERIAL IN YOUR PROCESS OR IN COMBINATION WITH OTHER SUBSTANCES



SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: OIL ONLY POLYPROPYLENE ABSORBENTS

PRODUCT USE: SORBENT MEDIA USED TO ABSORB OIL-BASED CHEMICALS WHICH INCLUDE BUT NOT LIMITED TO DIESEL FUEL, OIL, GASOLINE AND KEROSENE WHILE REPELLING WATER AND WATER BASED PRODUCTS.

SPECIFIC PRODUCT TYPE: ABSORBENT PADS

COMPANY INFORMATION: ENPAC, LLC
34355 MELINZ DRIVE
EASTLAKE, OH 44095

PHONE: 440-975-0070
FAX: 440-975-0047
EMER: 440-975-0070

SECTION 2: HAZARDS IDENTIFICATION

THIS PRODUCT IS NOT DANGEROUS IN ITS UNUSED FORM AND CONTAINS NO HAZARDOUS INGREDIENTS. NOT WHMIS REGULATED.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

MATERIALS	PERCENT	CAS #
POLYPROPYLENE:	>97%	9003-07-0
ANTI STATIC AGENT	<0.3%	NONE
WHITE PIGMENT	< 1%	NONE
PINK PIGMENT	<1%	NONE
BLUE PIGMENT	< 1%	NONE

SECTION 4: FIRST AID MEASURES

NO SPECIAL PROCEDURES REQUIRED

SECTION 5: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >315 DEGREES CELCIUS (ASTM D93)

FLAMMABLE LIMITS: NOT YET DETERMINED

EXTINGUISHING MEDIA: WATER, FOAM, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: STANDARD PROCEDURE FOR CLASS A FIRES

UNUSUAL FIRE AND EXPLOSION HAZARD: SOME CARBON MONOXIDE UNDER LEAN OXYGEN CONDITIONS

SECTION 6: ACCIDENTAL RELEASE MEASURES

NO SPECIAL STEPS ARE TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

SECTION 7: HANDLING AND STORAGE

STORE IN DRY AREA. DO NOT STORE NEAR OPEN FLAME, HIGH HEAT OR STRONG OXIDANTS. POLYPROPYLENE, WHEN HEATED, BECOMES VERY STICKY AND WILL BURN. USE SELF-CONTAINED AIR MASK TO ENTER SMOKY AREA IN THE EVENT OF FIRE.

SECTION 8: EXPOSUR CONTROLS/PERSONAL PROTECTIVE EQUIPMENT

EXPOSURE LIMITS: OSHA PEL: N/A **ACGIH TLV: N/A**

RESPIRATORY PROTECTION: NONE REQUIRED

VENTILATION: NONE REQUIRED

PROTECTIVE GLOVES: NONE REQUIRED ONLY IF MOLTAN

EYE PROTECTION: NONE REQUIRED

OTHER PROTECTIVE EQUIPMENT (SPECIFY): NONE REQUIRED

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

COLOR: WHITE, BLUE

DENSITY: 0.04 - 0.06 gram/cc

ODOR: NO ODOR

SPECIFIC GRAVITY: 0.88 - 0.92

FLASH POINT: NOT APPLICABLE

BOILING POINT: NOT APPLICABLE

MELTING POINT: > 160 DEGREES CELSIUS

SOLUBILITY IN WATER: INSOLUABLE

PERCENT VOLATILE:	NOT APPLICABLE
EVAPORATION RATE:	NOT APPLICABLE
VAPOR PRESSURE (mm Hg):	NOT APPLICABLE
VAPOR DENSITY (Air = 1):	NOT APPLICABLE
AUTO IGNITION TEMPERATURE	>675 DEGREES FAHRENHEIT

SECTION 10: STABILITY AND REACTIVITY DATA

STABILITY:	STABLE
INCOMPATIBILITY (conditions to avoid):	NONE
INCOMPATIBILITY (materials to avoid):	NITRIC ACID, PERCHLORIC ACID, SULFURIC ACID OR 98% SULFURIC ACID
HAZARDOUS DECOMPOSITON:	WHEN HEATED, IT MAY EMIT TOXIC
HAZARDOUS POLYMERAZATION:	WILL NOT OCCUR

SECTION 11: TOXOCOLOGICAL INFORMATION

HEALTH HAZARDS (acute or cronic):	NONE
SIGNS OR SYMPTOMS OF EXPOSURE:	NONE
MEDICAL CONDITIONS GENERRALLY AGGRAVATED BY EXPOSURE:	NONE
DATE ISSUED:	1/1/2018
PREPARED BY:	ENPAC, LLC

SECTION 12 TO SECTION 15 NOT APPLICABLE

SECTION 16: OTHER INFORMATION

SDS PREPARATION DATE: January 1, 2018

THE INFORMATION CONTAINED HEREIN IS ACCCURATE TO THE BEST OF MY KNOWLEDGE. MY COMPANY MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE SAFE USE OF THIS MATERIAL IN YOUR PROCESS O IN COMBINATION WITH OTHER SUBSTANCES



SAFETY DATA SHEET — 16 Sections

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier	[WHMIS Classification]
Perlite, Expanded, ENSORB Super Absorbent	Not Applicable
Product Use	
Industrial Absorbent	
Manufactured For:	
ENPAC, LLC	
Street Address	
34355 Melinz Parkway	
City, State, Postal Code	
Eastlake, Ohio 44095	
Emergency Telephone	
440-975-0070	
Date SDS Prepared	
1/1/2024	

SECTION 2 — HAZARDS IDENTIFICATION

Route of Entry	☒ Skin Contact	☐ Skin Absorption	☒ Eye Contact	☒ Inhalation	☐ Ingestion
Emergency Overview					
This product contains crystalline silica (less than .01%). OSHA considers perlite to be a nuisance dust. Inhalation of high amounts over long periods of nuisance dust may overload lung clearance mechanism and make the lungs more vulnerable to respiratory disease.					
WHMIS Symbols					
Not Regulated					
Potential Health Effects					
Inhalation: Pre-existing upper respiratory and lung disease may be aggravated. Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Chronic inhalation of dust should be avoided.					
Eye: May cause irritation (tear formation and redness) if dust gets in eyes.					
Skin: Not absorbed by the skin. But may cause dryness if prolonged exposure.					
Ingestion: Ingestion of small to moderate quantities is not considered harmful, but may cause irritation of the mouth, throat and stomach.					

SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients (specific)	%	CAS Number	LD ₅₀ of Ingredient (specify species and route)	LC ₅₀ of Ingredient (specify species)	OSHA PEL (mg/m ³)	ACGIH TLV (mg/m ³)
Perlite	100	93763-70-3	Not Available	Not Available	10	15
Silica/ Quartz	< 0.1	14808-60-7	Not Available	Not Available	Not Available	.05



SECTION 4 — FIRST AID MEASURES

Skin Contact
Use moisture renewing lotions if dryness occurs.
Eye Contact
Flush eyes with generous quantities of water or eye rinse solution. Consult physician if irritation persists.
Inhalation
Remove to fresh air. Blow nose to evacuate dust.
Ingestion
Drink generous amounts of water to reduce bulk and drying effects.

SECTION 5 — FIRE FIGHTING MEASURES

Flammable ☐ Yes ☒ No		If yes, under which conditions?
Means of Extinction N/A		
Flashpoint (° C) and Method None	Upper Flammable Limit (% by volume) None	Lower Flammable Limit (% by volume) None
Auto ignition Temperature (°C) Not Combustible	Explosion Data — Sensitivity to Impact N/A	Explosion Data — Sensitivity to Static Discharge N/A
Hazardous Combustion Products N/A		
NFPA N/A		

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Personal Precautions: If dust is present, use respirator fitted with particulate filter as specified in Section 8. Protect eyes with goggles.
Containment and Cleanup: Vacuum clean dust with equipment fitted with HEPA filter. Use dust suppressant such as water if sweeping is necessary.
Environment: Not considered as hazardous waste by RCRA (40 CFR Part 261). Place waste and spillage in closed containers. Dispose of in approved landfill.

SECTION 7 — HANDLING AND STORAGE

Handling Procedures and Equipment
Minimize dust generation. Avoid contact with eyes. Avoid breathing dust. Repair or dispose of broken bags.
Storage Requirements
Store in a dry place to maintain packaging integrity and product quality. Do not store near hydrofluoric acid. Observe all label precautions and warnings.



SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure Limits						
☒ ACGIH TLV		☒ OSHA PEL		☐ Other (specify)		
Specific Engineering Controls (such as ventilation, enclosed process)						
Adequate ventilation and appropriate local exhaust where needed to keep dust level below PEL.						
Personal Protective Equipment						
☒ Gloves		☒ Respirator		☒ Eye		☐ Footwear
				☐ Clothing		☐ Other
If checked, please specify type						
Eye: Goggles to protect from dust.						

Skin: No special equipment is required.

Respiratory: Respirators fitted with filters certified to standard 42CFR84 under series N95 should be worn when dust is present. If the dust concentration is less than ten (10) times the Permissible Exposure Limit (PEL) use a quarter or half mask respirator. If dust concentration is greater than ten (10) times and less than fifty (50) times the PEL, a full-face piece respirator fitted with replaceable N95 filters is recommended. If dust concentration is greater than fifty (50) and less than two-hundred (200) times the PEL use a power air-purify (positive pressure) respirator with replaceable N95 filter. If dust concentration is greater than two-hundred (200) times the PEL use a type C, supplied air respirator (continuous flow, positive pressure), with full face piece, hood or helmet.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Odor and Appearance	Odor Threshold (ppm)
Solid	White Granules or Powder. No distinct odor.	N/A
Specific Gravity	Vapor Density (air = 1)	Vapor Pressure (mmHg)
2.35	N/A	N/A
Evaporation Rate	Boiling Point (° C)	Freezing Point (° C)
N/A	N/A	N/A
pH	Coefficient of Water/Oil Distribution	[Solubility in Water]
6-10	N/A	Slightly Soluble



SECTION 10 — STABILITY AND REACTIVITY

Chemical Stability ☒ Yes ☐ No	If no, under which conditions?
Incompatibility with Other Substances ☒ Yes ☐ No	If yes, which ones? Reacts with Hydrofluoric Acid to form Silicon Tetrafluoride gas
Reactivity and under what conditions? No dangerous reactions known.	
Hazardous Decomposition Products None	

SECTION 11 — TOXICOLOGICAL INFORMATION

Effects of Acute Exposure	
Potential irritant for skin contact, eye contact or inhalation.	
Effects of chronic exposure	
Perlite is a naturally occurring volcanic glass consisting of fused sodium-potassium-aluminum silicate. Tests conducted on Perlite have not identified crystalline silica as being present above the detection limit (0.05%). Although there are not published reports of adverse health effects from exposure to perlite dust, dust levels should be maintained below the OSHA Permissible Exposure Limit for perlite and respirators used when airborne dust is present.	
Irritancy of Product	
Potential irritant for skin contact, eye contact or inhalation.	
Skin sensitization Possible through skin contact.	Respiratory sensitization
Carcinogenicity-IARC N/A	Carcinogenicity - ACGIH N/A
Reproductive toxicity N/A	Teratogenicity N/A
Embrototoxicity N/A	Mutagenicity N/A
Name of synergistic products/effects N/A	

SECTION 12 — ECOLOGICAL INFORMATION

Aquatic Toxicity
Generally considered inert. Perlite has no negative ecological effect and may be used as a soil container.

SECTION 13 — DISPOSAL CONSIDERATIONS

Waste Disposal
Not considered hazardous waste by the RCRA (40 CFR Part 261). Place waste and spillage in closed containers.
Dispose in accordance with Federal, State and Local regulations.

SECTION 14 — TRANSPORT INFORMATION

Special Shipping Information		
No known shipping regulations.		
		PIN
		N/A
TDG	DOT	
N/A	N/A	
IMO	ICAO	
N/A	N/A	

SECTION 15 — REGULATORY INFORMATION

WHMIS Classification	OSHA
Not regulated	Perlite is not considered as a toxic or hazardous subject.
SERA	TSCA
Not Listed	Not Listed.
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.	

SECTION 16 — OTHER INFORMATION

Notice: This information relates only to the material designated and may not be valid for such material used in combination with any other materials or in any process. All statements, information and data provided are believed to be accurate and reliable, but are presented without any guarantee, representation, warranty or responsibility of any kind, expressed or implied. Any and all representations and/or warranties of merchantability of fitness for a particular purpose are specifically disclaimed. Users should make their own investigations as to the suitability of the information or product for their particular purpose. Nothing in this document is intended as permission, inducement or recommendation to violate any laws or practice any invention covered by existing patents, copyrights or inventions. ENPAC,LLC. does not accept liability for any loss or damage that may occur from the use of this information.