

POLY-TANK CONTAINMENT UNIT/275™



For the widely-used 275-gallon obround tank, Poly-Tank Containment Unit/275™ helps protect against hazardous and costly spills. Poly-Tank 275 is designed to save space and provide easy access to the tank and pump preventing harmful spills from contaminating your yard. Optional fitted tarp (Part #: 5275-TARP) and trickle filter (Bazooka).



(see Tarp on page 13)

POLY-TANK CONTAINMENT UNIT/275™

Part #	Description	Ext. Dimension L x W x H in. (cm)	Int. Top Dimension in. (cm)	Int. Bottom Dimension (cm)	Weight lb. (kg)	Spill Cap. gal. (L)
5275-BK	Poly-Tank	82 x 45 x 35.38 (208 x 114 x 90)	77 x 39.5 (196 x 188)	66 x 29 (168 x 74)	98 (44.5)	275 (1,041)
5275-BK-D	(w/drain)					
5275-TARP	Tarp	82.25 x 45 x 45.5 (208.9 x 114 x 115.5)			10 (4.5)	

Regulations: EPA 40 CFR 264.175, SPCC, NPDES and UFC

POLY-TANK CONTAINMENT UNIT/550™

KEEP HAZARDOUS LIQUID STORED SAFELY ABOVE THE GROUND.

Designed for the 550-gallon skid tank, (and 150-gallon, 300-gallon skid elevated tanks) this unit safely protects against hazardous liquid discharge into the ground. Large interior leaves space for hoses and related equipment. Ideal for construction sites, marine, and farm use. Optional fitted tarp (Part #: 5550-TARP), drain (5551), and trickle filter (Bazooka).



POLY-TANK CONTAINMENT UNIT/550™

Part #	Description	Dimensions L x W x H in. (cm)	Weight lb. (kg)	Spill Cap. gal. (L)
5550-BK	Forkliftable	113 x 71 x 32 (287 x 180 x 81)	190 (86.2)	750 (2,082)
5550-BK-D	(w/drain)			
5550-TARP	Tarp	115 x 75 x 50.5 (292 x 190.5 x 128)	12 (5.5)	

EPA 40 CFR 264.175, SPCC, NPDES and UFC



(see Tarp on page 13)



BULKHEAD FITTINGS™

Optional bulkhead fittings make pumping and draining fast and easy. (For Part # 5275-BK and 5550-BK)

BULKHEAD FITTING

Part #	Dimensions Ext. Dia in. (cm)	Connection Dimensions in. (cm)	Weight lb. (kg)
5276	3 (Ø)	.75 (Ø)	1 (.5)



(See Bazooka on page 25.)