

ibcBERM

FLEXIBLE IBC TOTE SPILL CONTAINMENT

The ENPAC iBcBERM uses a unique L-Bracket sidewall support system mounted on the exterior leaving the interior free from interference. Removable L-Brackets allow sidewalls to lay flat for entry and exit. Made from rugged resistant PVC and replaceable L-Brackets, this berm is convenient for containing IBC units or any application that requires a durable, long lasting, portable containment unit.



STINGER BERM

Part #	Description	Ext. Dimension L x W x H ft. (m)	Weight lb. (kg)	Spill Cap. gal. (L)
48-452-YE-SS	L-Bracket	4 x 5 x 2 (1.2 x 1.5 x .6)	84 (38.1)	299 (1131.84)
48-462-YE-SS	L-Bracket	4 x 6 x 2 (1.2 x 1.8 x .6)	100 (45.4)	359 (1358.96)
48-552-YE-SS	L-Bracket	5 x 5 x 2 (1.5 x 1.5 x .6)	102 (46.3)	374 (1415.74)

Regulations: EPA 40 CFR 264.175, SPCC, NPDES and UFC

POLY-EDGE™

MULTI-FUNCTIONAL STORAGE UNIT OFFERS TRANSPORTABLE CONVENIENCE.

The Poly-Edge™ can be used as a truck-mounted carrier spill response unit or wall-mounted unit in applications such as manufacturing facilities, laboratories and hospitals.

The lockable, large capacity unit offers versatile storage for tools and absorbents as well as ENPAC® Stinger Berms™ and Prowler™ Pools.

- Will not rust or corrode.
- Constructed of lightweight 100% polyethylene.
- Available in black and yellow
- Slotted footprint makes mounting easy.
- A special weather and water-resistant gasket keeps stored items dry.
- The perfect truck Spill Kit container! See details on page 46.



POLY-EDGE™

Part #	Description	Dimensions L x W x H in. (cm)	Weight lb. (kg)	Moulding Slots in. (cm)	Load Cap. lb. (kg)
1601-BK	Black	35 x 20 x 16 (89 x 51 x 41)	14 (6)	.625 (1.6)	75 (34)
1601-YE	Yellow	35 x 20 x 16 (89 x 51 x 41)	14 (6)	.625 (1.6)	75 (34)

