

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: AGGRESSIVE/HAZMAT POLYPROPYLENE ABSORBENTS

PRODUCT USE: SORBENT MEDIA USED TO ABSORB LEAKS AND SPILLS WHICH INCLUDE BUT NOT LIMITED TO OIL, WATER,

COOLANTS AND SOLVENTS

SPECIFIC PRODUCT TYPE: ABSORBENT PADS

COMPANY INFORMATION: ENPAC, LLC PHONE: 440-975-0070

34355 MELINZ DRIVE FAX: 440-975-0047 EASTLAKE, OH 44095 EMER: 440-975-0070

SECTION 2: HAZARDS IDENTIFICATION

THIS PRODUCT IS NOT DANGEROUS IN ITS UNUSED FORM AND CONTAINS NO HAZARDOUS INGREDIENTS. NOT WHMIS REGULATED.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

MATERIALS	PERCENT	CAS#
POLYPROPYLENE:	>97%	9003-07-0
SURFACTANT:	< 1%	9004-34-6
GRAY PIGMENT	< 1%	NONE
YELLOW PIGMENT	< 1%	NONE
GREEN PIGMENT	< 1%	NONE
ORANGE PIGMENT	< 1%	NONE

SECTION 4: FIRST AID MEASURES

NO SPECIAL PROCEDURES REQUIRED

SECTION 5: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >315 DEGREES CELCIUS (ASTM D93)

FLAMMABLE LIMITS: NOT YET DETERMINED

EXTINGUISHING MEDIA: WATER, FOAM, CO2, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: STANDARD PROCEDURE FOR CLASS A FIRES

UNUSUAL FIRE AND EXPLOSION HAZARD: SOME CARBON MONOXIDE UNDER LEAN OXYGEN CONDITIONS

SECTION 6: ACCIDENTAL RELEASE MEASURES

NO SPECIAL STEPS ARE TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

SECTION 7: HANDLING AND STORAGE

VENTILATION:

STORE IN DRY AREA. DO NOT STORE NEAR OPEN FLAME, HIGH HEAT OR STRONG OXIDANTS. POLYPROPYLENE, WHEN HEATED, BECOMES VERY STICKY AND WILL BURN. USE SELF-CONTAINED AIR MASK TO ENTER SMOKY AREA IN THE EVENT OF FIRE.

SECTION 8: EXPOSUR CONTROLS/PERSONAL PROTECTIVE EQUIPMENT EXPOSURE LIMITS: OSHA PEL: N/A ACGIH TLV: N/A

RESPIRATORY PROTECTION: NONE REQUIRED

PROTECTIVE GLOVES:

NONE REQUIRED

ONLY IF MOLTAN

NONE REQUIRED

EYE PROTECTION:

OTHER PROTECTIVE EQUIPMENT (SPECIFY):

NONE REQUIRED

NONE REQUIRED

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

COLOR: GRAY, YELLOW, GREEN, ORANGE

DENSITY: 0.04 - 0.06 gram/cc

ODOR: CITRUS (IN ORANGE ABSORBENT)

SPECIFIC GRAVITY: 0.88 - 0.92

FLASH POINT: NOT APPLICABLE

BOILING POINT: NOT APPLICABLE

MELTING POINT: > 160 DEGREES CELSIUS

SOLUBILITY IN WATER: INSOLUBLE
PERCENT VOLATILE: NOT APPLICABLE
EVAPORATION RATE: NOT APPLICABLE
VAPOR PRESSURE (mm Hg): NOT APPLICABLE
VAPOR DENSITY (Air = 1): NOT APPLICABLE

AUTO IGNITION TEMPERATURE >675 DEGREES FAHRENHEIT

SECTION 10: STABILITY AND REACTIVITY DATA

STABILITY: STABLE INCOMPATIBILITY (conditions to avoid): NONE

INCOMPATIBILITY (materials to avoid): NITRIC ACID, PERCHLORIC ACID, SULFURIC ACID OR 98% SULFURIC ACID

HAZARDOUS DECOMPOSITON: WHEN HEATED, IT MAY EMIT TOXIC

HAZARDOUS POLYMERAZATION: WILL NOT OCCUR

SECTION 11: TOXOCOLOGICAL INFORMATION

HEALTH HAZARDS (acute or cronic):

SIGNS OR SYSMPTOMS OF EXPOSURE:

MEDICAL CONDITIONS GENERRALLY AGGRAVATED BY EXPOSURE:

NONE

DATE ISSUED: January 1, 2018
PREPARED BY: ENPAC, LLC

SECTION 12 TO SECTION 15 NOT APPLICABLE

SECTION 16: OTHER INFORMATION

SDS PREPARATION DATE: January 1, 2018

THE INFORMATION CONTAINED HEREIN IS ACCCURATE TO THE BEST OF MY KNOWLEDGE. MY COMPANY MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE SAFE USE OF THIS MATERIAL IN YOUR PROCESS OR IN COMBINATION WITH OTHER SUBSTANCES