



SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: OIL ONLY POLYPROPYLENE ABSORBENTS
PRODUCT USE: SORBENT MEDIA USED TO ABSORB OIL-BASED CHEMICALS WHICH INCLUDE BUT NOT LIMITED TO DIESEL FUEL, OIL, GASOLINE AND KEROSENE WHILE REPELLING WATER AND WATER BASED PRODUCTS.
SPECIFIC PRODUCT TYPE: ABSORBENT PADS
COMPANY INFORMATION: ENPAC, LLC
34355 VOKES DRIVE
EASTLAKE, OH 44095
PHONE: 440-975-0070
FAX: 440-975-0047
EMER: 440-975-0070

SECTION 2: HAZARDS IDENTIFICATION

THIS PRODUCT IS NOT DANGEROUS IN ITS UNUSED FORM AND CONTAINS NO HAZARDOUS INGREDIENTS.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

MATERIALS	PERCENT	CAS #
POLYPROPYLENE:	>97%	9003-07-0
ANTI STATIC AGENT	<0.3%	NONE
WHITE PIGMENT	< 1%	NONE
PINK PIGMENT	<1%	NONE
BLUE PIGMENT	< 1%	NONE

SECTION 4: FIRST AID MEASURES

NO SPECIAL PROCEDURES REQUIRED

SECTION 5: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >315 DEGREES CELCIUS (ASTM D93)
FLAMMABLE LIMITS: NOT YET DETERMINED
EXTINGUISHING MEDIA: WATER, FOAM, CO2, DRY CHEMICAL
SPECIAL FIRE FIGHTING PROCEDURES: STANDARD PROCEDURE FOR CLASS A FIRES
UNUSUAL FIRE AND EXPLOSION HAZARD: SOME CARBON MONOXIDE UNDER LEAN OXYGEN CONDITIONS

SECTION 6: ACCIDENTAL RELEASE MEASURES

NO SPECIAL STEPS ARE TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

SECTION 7: HANDLING AND STORAGE

STORE IN DRY AREA. DO NOT STORE NEAR OPEN FLAME, HIGH HEAT OR STRONG OXIDANTS. POLYPROPYLENE, WHEN HEATED, BECOMES VERY STICKY AND WILL BURN. USE SELF-CONTAINED AIR MASK TO ENTER SMOKY AREA IN THE EVENT OF FIRE.

SECTION 8: EXPOSUR CONTROLS/PERSONAL PROTECTIVE EQUIPMENT

EXPOSURE LIMITS: OSHA PEL: N/A **ACGIH TLV: N/A**

RESPIRATORY PROTECTION: NONE REQUIRED
VENTILATION: NONE REQUIRED
PROTECTIVE GLOVES: NONE REQUIRED ONLY IF MOLTAN
EYE PROTECTION: NONE REQUIRED
OTHER PROTECTIVE EQUIPMENT (SPECIFY): NONE REQUIRED

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

COLOR: WHITE, BLUE
DENSITY: 0.04 - 0.06 gram/cc
ODOR: NO ODOR
SPECIFIC GRAVITY: 0.88 - 0.92
FLASH POINT: NOT APPLICABLE
BOILING POINT: NOT APPLICABLE
MELTING POINT: > 160 DEGREES CELSIUS
SOLUBILITY IN WATER: INSOLUABLE

PERCENT VOLATILE: NOT APPLICABLE
EVAPORATION RATE: NOT APPLICABLE
VAPOR PRESSURE (mm Hg): NOT APPLICABLE
VAPOR DENSITY (Air = 1): NOT APPLICABLE
AUTO IGNITION TEMPERATURE >675 DEGREES FAHRENHEIT

SECTION 10: STABILITY AND REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (conditions to avoid): NONE
INCOMPATIBILITY (materials to avoid): NITRIC ACID, PERCHLORIC ACID, SULFURIC ACID OR 98% SULFURIC ACID
HAZARDOUS DECOMPOSITION: WHEN HEATED, IT MAY EMIT TOXIC
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

HEALTH HAZARDS (acute or chronic): NONE
SIGNS OR SYMPTOMS OF EXPOSURE: NONE
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: NONE
DATE ISSUED: November 19, 2014
PREPARED BY: ENPAC, LLC

SECTION 12 TO SECTION 15 NOT APPLICABLE

SECTION 16: OTHER INFORMATION

SDS PREPARATION DATE: November 19, 2014

THE INFORMATION CONTAINED HEREIN IS ACCURATE TO THE BEST OF MY KNOWLEDGE. MY COMPANY MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE SAFE USE OF THIS MATERIAL IN YOUR PROCESS IN COMBINATION WITH OTHER SUBSTANCES