

## Storm Sentinel Curb Inlet Filter

### SKU# 4346



Storm Sentinels are the ideal products for preventing harmful pollutants from washing into storm drains. The Curb Inlet Filter features a rigid coiled center wrapped in non-woven geotextile. Stormwater easily passes through the coiled filter, preventing sediment and other pollutants from entering the catch basin. The coil remains rigid after installation, allowing the unit to maintain its position and filtration even during the largest storm events. The 4'L x 5" Diameter is a standard size suitable for most applications, but custom sizes are also available upon request. Installation (detailed below) will vary based on curb inlet type, but complete solutions are available for full protection and compliance!

For full protection and best performance, the Curb Inlet Filter (4346) is combined with a drop inlet filter for Curb + Drop Inlet drains, or with weighted filter bags for Curb Inlet ONLY drains. The differences are illustrated below.

Technical Data		
	U.S.	Metric
<b>Dimensions</b>	48" x 5" diameter	121.9 cm x 12.7 cm diameter
<b>Unit Weight</b>	5 lbs	2.26 kg
<b>Flow Rate</b>	90 gpm/ft <sup>2</sup>	3667 Lpm/m <sup>2</sup>
<b>Material</b>	8 oz. Non-woven Geotextile	
<b>Regulations</b>	EPA, SPCC and NPDES	