

Q-VAC 100X SKU# QVAC100-X



*55-Gal Steel drum and scooter are not included

The Q-VAC 100X is designed to pick up liquids in environments that require explosion proof equipment. It has no electrical parts and is air driven. The only threat of explosion comes from static electricity build up. The Q-VAC 100X is designed to eliminate the possibility of static electricity build up and discharge. The entire unit from floor tool to the hooded Venturi is grounded. The connection fittings and floor tool are made of conductive aluminum. The hose uses conductive wire and the wand is constructed of plated steel. Combined with the Venturi and drum lid, they form a complete circuit which sheds any static electricity to ground via a spring loaded alligator clamp (attached by the user to a reliable ground).

Easy to use and highly reliable, the Q-VAC 100X pumps liquid directly into a standard drum for convenient storage or recycling. A liquid overflow shutoff valve ensures vacuum automatically turns off when the drum is full.

- Minimizes use of absorption materials
- Fits on a standard 55 gal., closed top drum
- Requires no filters
- No moving parts to break or replace

Technical Data		
	U.S.	Metric
Dimensions	34" L x 37" W x 9" H	86.3 x 94 x 22.8 cm
Unit Weight	34 lbs	15.4 kg
Regulations	40 CFR 112.7, 40 CFR 122.26, 29 CFR 1910.22(a)(2)	

Options & Accessories		
QVAC 100 Plus (w/ Scooter)	QVAC PLUS	
QVAC 100	QVAC100	
Scooter	5205-YE	

Phone: 800-936-7229 E-mail: info@ENPAC.com www.ENPAC.com ENPAC, LLC 34355 Melinz Parkway Eastlake, OH 44095